

Orona 3G

X-37C

Car Lifts


Hydraulic drive solution for car transport

Hydraulic drive solution for heavy and/or delicate loads.

General specifications

Load / Capacity	3,500 to 5,000 kg
Speed	0.2 - 0.5 m/s
Maximum travel	21 m
Maximum floors served	7 floors
Entrances	1 front / 2 open through
Drive system	Hydraulic
Controller	ARCA III controller, low energy consumption multiprocessor
Door types	Automatic side-opening / Automatic central-opening
Clear door opening	From 2,200 to 2,900 mm (in 100 mm increments)
Door height	2,000 / 2,100 / 2,200 / 2,300
Car dimensions	Parametric car dimensions
Internal car height	2,200 / 2,300 / 2,400 / 2,500
Aesthetic solutions	Heavy loads Aesthetics

Standard Optional



1 HYDRAULIC LIFTS

The hydraulic systems, renowned for their long life cycle, are very versatile and offer convenient solutions to heavy load requirements or reduced shaft spaces.



2 PARAMETRIC/FLEXIBLE

Flexible car and door configurations ensure available shaft dimensions can be optimised.



3 ROBUST LIFT CAR

Provides greater comfort during lift travel, with reduced vibration and noise.



4 CARS

Special car dimensions, with extra depth and wider doors. Designed with reinforced panels and floors for multiple and intensive uses.



ECO-EFFICIENCY



ADAPTABILITY



DESIGN AND ACCESSIBILITY



CONTROL AND SAFETY

